

## Power Strip CPPS\*6-TT (EU)



IN: 1x powerCON TRUE1 TOP IN – OUT: 6 x Schuko, 1x powerCON TRUE1 TOP

Power Strip is a reliable power distribution solution for indoor applications. Equipped with 1x powerCON® TRUE1® TOP IN, up to 6x Schuko OUT and 1x powerCON® TRUE1® TOP OUT for daisy chaining.

### Features & Benefits

Highly reliable NEUTRIK® powerCON® recepticals for In and daisy chaining

Light weight, compact housing

Several mounting options

### Market & applications

- ✓ Markets: Professional video wall / lighting / audio
- ✓ Semi-permanent applications: Theaters, studios,..
- ✓ Permanent installations: Lecture hall, auditorium, classrooms,..

### Article Variations

Article name	Details
CPPSF6-TT	IN: 1x powerCON® TRUE1® TOP - OUT: 6x Schuko type F OUT and 1x powerCON®
CPPSE6-TT	IN: 1x powerCON® TRUE1® TOP - OUT: 6x Schuko type E OUT and 1x powerCON®

## Technical Information

Product	
Input device	1 x powerCON® TRUE1® TOP
Output device	CPPSE6-TT: 6x Schuko Typ E CPPSF6-TT: 6x Schuko Type F
Daisy chaining	1x powerCON® TRUE1® TOP

Electrical	
Contact resistance / protection class	Protection class II
Dielectric strength	0,5 kV / mm
Rated voltage	250V AC
Rated Current	16A
Number of electrical contacts	2 + PE
Phases	single-phase

## Mechanical

Dimensions	398 x 60 x 46.6 mm
------------	--------------------

Conductor cross section	Daisy chaining: 2.5 mm <sup>2</sup> Schuko; 1.5 mm <sup>2</sup>
-------------------------	--

Weight	0.43 kg
--------	---------

Mounting options	mounting wholes
------------------	-----------------

## Material

Housing	PVC
---------	-----

Color	black
-------	-------

## Environmental

Protection class	IP20
------------------	------

Temperature range	-5 °C bis +40 °C
-------------------	------------------